

BARRACUDA UNDER REAMER

(U.S.A. Patent No.: US 6,561,286)

BARRACUDA UNDER REAMER SPECIFICATIONS:					
OD	1.750"	2.125"	2.375"	2.875"	3.750"
ID	0.406	0.500"	0.500"	0.625"	0.625"
Milling Blade Range: Pipe OD	4.0" thru 5.0"	5.0" thru 7.0"	5.0" thru 7.0"	5.5" thru 7.0"	6.625" thru 9.625"
Max. Operating Temperature	200° C	200° C	200° C	200° C	200° C
Maximum Allowable Pull	17,000 lbs.	18,050 lbs.	18,050 lbs.	39,000 lbs.	44,000 lbs.
Maximum Flow Rate	1.5 BBL/min.	2.5 BBL/min.	2.5 BBL/min.	3.5 BBL/min.	6.5 BBL/min.
Maximum Allowable Torque	360 ft. lbs.	500 ft. lbs.	500 ft. lbs.	600 ft. lbs.	1,000 ft. lbs.
Safe Working Pressure	5,000 PSI	5,000 PSI	5,000 PSI	5,000 PSI	5,000 PSI
Maximum Tool Length	11.35"	12.5"	12.5"	13.25"	16.27"
Connection: Box	1.375"-10-TPI-SA	1.800"-10-TPI-SA	1.800"-10-TPI-SA	2.250"-10-TPI-SA	3.000"-8-TPI-SA-2G

Although the material contained herein was in effect at the time of publication, certain changes or modifications in design may have been made since its release to meet ever-increasing industry demands. Global Tools Limited reserves the right to make these product changes without notice, and without incurring any liability or obligation. Contact your nearest Global Tools Limited representative for any updates concerning this product.