

RHINO CENTRALIZER TOOL SPECIFICATIONS

| RHINO CENTRALIZER SPECIFICATIONS | | | | | |
|----------------------------------|------------------------|----------------------|----------------------|------------------|-------------------------|
| Model Number | CEN-175-AO1 | CEN-212-AO1 | CEN-237-AO1 | CEN-NR-287-AO1 | CEN-425-AO1 |
| OD | 1.750" | 2.125" | 2.375" | 2.875" | 4.250" |
| ID | 0.375 | 0.500" | 0.500" | 0.500" | 0.625" |
| Blade Range | 2-3/8" TO 4-1/2" | 2-7/8" TO 6-5/8" | 2-7/8" TO 6-5/8" | 4.0" THRU 8.625" | 4-1/2" TO 9-5/8" |
| Max. Operating Temperature | 450° C | 450° C | 450° C | 200° C | 450° C |
| Maximum Allowable Pull | 10,000 lbs. | 15,000 lbs. | 15,000 lbs. | 16,000 lbs. | 17,000 lbs. |
| Maximum Flow Rate | 30 G.P.M. | 100 G.P.M. | 100 G.P.M. | 2.5 BBM/MIN | 150 G.P.M. |
| Maximum Allowable Torque | 583 ft. lbs. | 684 ft. lbs. | 1363 ft. lbs. | 2,275 ft. lbs. | 3,893 ft. lbs. |
| Safe Working Pressure | 5,000 PSI | 5,000 PSI | 5,000 PSI | 5,000 PSI | 5,000 PSI |
| Maximum Tool Length | 18" | 18" | 18" | 20.62" | 26.75" |
| Connection: Box | 1.375"-10-SA Pin x Box | 1.8"-10-SA Pin x Box | 1.8"-10-SA Pin x Box | 2.25"-10-TPI-SA | 3.00"-8-SA-2G Pin x Box |
| Recommended make-Up Torque | 350 (ft.lb) | 450 (ft.lb) | 850 (ft.lb) | 1,400 (ft.lb) | 2,500 (ft.lb) |

Although the material contained herein was in effect at the time of publication, certain changes or modifications in design may have been made since its release to meet ever-increasing industry demands. Global Tools Limited reserves the right to make these product changes without notice, and without incurring any liability or obligation. Contact your nearest Global Tools Limited representative for any updates concerning this product.